

PRESSURE WASHER HOSE



PRESSURE WASHER HOSE ARM-A-FLEX™ (HOT-WATER)

It's an undeniable fact: Most rubber pressure washer hoses wear from the outside in, rather than the inside out. And in some applications that can happen way too fast. Wooden decks, asphalt roofs and surfaces and concrete. They can all tear up a hose cover. Introducing ProPulse™ Arm-a-Flex™ with a specially engineered ultra-high molecular weight jacket designed to extend hose cover life by up to ten times.

NOT FOR STEAM

- › Connectors: SOLxSWV
- › Reinforcement: Two-Layer Wire Braid
- › Cover: UHMWPE Ultra-High Molecular Weight Polyethylene
- › Inner Diameter: 3/8"
- › Working (Maximum): 4785 PSI
- › Burst (Min) 4:1 Working Pressure
- › Impulse Life: 200,000+
- › Temperature (Max): 250°F
- › Volume Discounts: Quantities of 20, 30, 40, 50, 100, 200 and 300

COMMERCIAL ARM-A-FLEX | 3/8" 4785PSI (250°) (2-Wire Braid)

Item Code	Description
989400258	ARM-A-FLEX BLACK 3/8"x50' 4785PSI SOLxSWV 2BR
989400272	ARM-A-FLEX BLACK 3/8"x100' 4785PSI SOLxSWV 2BR



BLACK

