VALVES

V100SL V150SL



V200SL

| 3 WAY SIDE LOAD VALVES | | | | | | | | |
|------------------------|--------------------------------|------------|--------------|-------------------------|------------|----------------|-----------------------|---------------|
| PART NO | DESCRIPTION | MAX PSI | PIPE SIZE | OPENING THRU BALL | LOT QTY | HANDLE TYPE | REPLACEMENT HANDLE | REPAIR KIT |
| V075SL | 3/4" 3-WAY SIDE LOAD VALVE | 200 | 3/4" | 1" | 6 | STRAIGHT | V10153A | V10300SL |
| V100SL | 1" FP 3-WAY SIDE LOAD VALVE | 200 | 1" | 1" | 6 | STRAIGHT | V10153A | V10300SL |
| V125SL | 11/4" 3-WAY SIDE LOAD VALVE | 300 | 11/4" | 1½" | 6 | Т | N/A | V15300SL |
| V150SL | 11/2" FP 3-WAY SIDE LOAD VALVE | 225 | 1½" | 1½" | 6 | Т | N/A | V15300SL |
| V200SL | 2" FP 3-WAY SIDE LOAD VALVE | 225 | 2" | 2" | 8/BOX | STRAIGHT | V25153SH | V25200BL |

3 WAY SIDE LOAD BALL VALVES

FEATURES

- Stainless steel bolts
- Precision molded in fiberglass reinforced polypropylene for additional strength
- Self-aligning ball moves freely against the PTFE seats for smooth operation
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats
- PTFE self-lubricating stem bushings and seats
- FKM body seals
- Directional flow, right or left.
 Valve cannot be turned off to stop flow

